Print your cards and badges **on demand**!

The printer that delivers personalized cards in small runs

Tattoo2 is the ideal solution for printing single-sided cards, individually or in small runs.

Tattoo2 is a multi-feature printer that prints texts, logos and barcodes in less than a minute, in color or monochrome, and can also encode magnetic stripes.

Designed to deliver a few hundreds of cards per year, **Tattoo2** offers an attractive quality / price ratio, and outperforms all other competing printers.

COMPACT AND SMART



Tattoo2 is a compact printer, with a size no larger than an A4 page. It can easily be deployed behind a counter or on a reception desk.

Tattoo2 comes with a detachable card feeder and with a front side feeding mode to personalize cards by the unit.

APPLICATIONS

Users who are looking for a simple and high-quality solution for their badges will adopt **Tattoo2**. Today, hundreds of small businesses, retail shops, clubs, associations, cities and schools rely on **Tattoo2** to deliver:

- Employee badges
- Membership cards for clubs and associations
- School cards
- Customer and loyalty cards
- Library cards
- Business cards
- Cards for youngsters or seniors













Tattoo



BENEFITS

■ Simple and user-friendly

Tattoo2 is both easy to install and easy to use. No training is necessary to run the printer.

All operations and maintenance tasks such as cleaning the printer, replacing a ribbon or reloading cards were therefore made effortless for the user.

■ A compact and follow-me printer

Tattoo2 is the most compact printer in its category. Its travel case, available as an option, makes it possible to carry this light-weight printer wherever you go, and use it whenever needed.

■ From basic to advanced cards

From thin cards to thicker payment cards, **Tattoo2** supports all your requirements. **Tattoo2** prints on plastic when long-lasting cards are required, but also on paper when your budget is tight.

Professional options

With Tattoo2, you can issue professional badges, with a resolution of 300 dpi, and benefit from a TCP/IP port, available as an option. Tattoo2 also supports multiple magnetic encoders.





lattooe	Your badges and cards made easy. Tattoo2.
SPECIFICATIONS	 Color printing module, 300 dpi print head (11.8 dots/mm) USB connection (cable supplied) 16 MB of RAM Detachable feeder with a capacity of 100 cards (0.76 mm or 30 mil) Output hopper with a capacity of 15 cards (0.76 mm or 30 mil) Automated adjustment of card thickness Control panel with 1 button and 4 LEDs Cover color: Fire Red RoHS-compliant
PRINTING	 Color-dye sublimation and monochrome thermal transfer Integrated ribbon saver for monochrome printing
OPTIONS & ACCESSORIES	 Ethernet TCP-IP, available as an option Magnetic stripe encoder ISO 7811 HiCo/LoCo or JIS2 Additional 10O-card feeder Manual card feeder Travel case Cleaning kit
RIBBONS	 5-panel YMCKO color ribbon: 100 cards/roll Monochrome ribbons: - up to 600 cards/roll (black, red, green, blue) - up to 500 cards/roll (white, gold and silver) BlackWAX monochrome ribbon (for ABS & special varnish plastic cards): up to 600 cards/roll
PRINTING SPEED	Color (YMCKO): 40 sec per cardMonochrome: 7 sec per card
CARD LOADING	Manual (card by card)Card feeder with delivery in output hopper
CARD FORMAT	■ ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")
CARD TYPE	■ All PVC, Composite PVC cards, PET, ABS¹ and special varnish¹ cards
CARD THICKNESS	■ From 0.25 mm² (10 mil) to 1 mm (40 mil)
RESIDENT FONTS	Arial 100, Arial bold 100Barcode: Code 39, 2/5 interlaced
SUPPORTED PLATFORMS	 Windows™ 7, XP and Vista (32 & 64 bits) Drivers for Windows™ 2003 and 2000 available on demand Macintosh™ 0S X v10.2 – 10.6 Linux
SOFTWARE	 eMedia Card Designer Software for designing and editing badges, 30-day free trial Compatible with Windows™ 7, XP, Server 2003 and Vista 32 & 64 bits
INTERFACE	■ USB port (cable supplied), Ethernet TCP-IP available as an option
SIZE OF THE PRINTER	 Without output hopper: Height: 166 mm (6.53") – 368 mm (14.49") – Width: 187 mm (7.36") With output hopper: Height: 166 mm (6.53") – Length: 368 mm (14.49") – Width: 187 mm (7.36")
WEIGHT OF THE PRINTER	■ 2.4 Kg (5.3 Lbs)
POWER SUPPLY	 Power supply: 100-240 V AC, 50-60 Hz, 1.5 or 1.8 A Printer: 24 V DC, 3 A
ENVIRONMENT	 Min/max operating temperature: 15° / 30°C (59° / 86°F) Humidity: 20% to 65% non-condensing Min/max storage temperature: -5° / +70°C (23° / 158°F) Storage humidity: 20% to 70% non-condensing Operating ventilation: free air

EUROPE, MIDDLE-EAST, AFRICA

Operating ventilation: free air

■ 3 years (printer and print head), unlimited printouts³

Under specific conditions.
 0.25 mm (10 mil) cards should be used only for printing in monochrome
 Warranty subject to observance of specific conditions and use of Evolis genuine consumables

WARRANTY

Evolis Card Printer \cdot 14, avenue de la Fontaine \cdot Z.I. Angers Beaucouzé \cdot 49070 Beaucouzé \cdot France Tel: + 33 (0) 241 367 606 · Fax: + 33 (0) 241 367 612 · info@evolis.com

 $\textbf{AMERICAS} \cdot \textbf{Evolis Inc.} \cdot \textbf{Fort Lauderdale} \cdot \textbf{evolisinc@evolis.com}$ $\textbf{ASIA-PACIFIC} \cdot \textbf{Evolis Asia Pte Ltd} \cdot Singapore \cdot evolisasia@evolis.com$ $\textbf{CHINA} \cdot \textbf{Evolis} \cdot \textbf{Sales office} \cdot \textbf{Shenzhen} \cdot \textbf{infochina@evolis.com}$ JAPAN · Evolis · Representative office · Tokyo · infojapan@evolis.com

